



# LUCHISMART VISUAL-PRO

POWERED WITH



WiFi Video Intercom Access  
Intercom

- > 2.4G WiFi connection,
- > Android and iOS available
- > Full duplex voice intercom
- > 2MP+wide angle camera and night vision
- > Support TF card with unlimited capacity
- > Support motion detection, playback, take picture/video, unlock remotely

Access Control

- > Touch key with one relay, 1000 users (988 common+2 panic+10 visitor)
- > PIN Length: 4~6 digits
- > EM card, Mifare card optional
- > Wiegand 26~44 bits in put & output
- > Can be used as Wiegand reader with LED & buzzer
- > User data can be transferred
- > 2 devices can be interlocked for 2 doors

[www.luchismart.com](http://www.luchismart.com)



USA: +12532990521




NIG: +23418880441



Sales@luchismart.com



# VISUAL-PRO SPECIFICATION



Product Size



Gift Box Size

Network	2.4G WiFi connection
Pixel	2.0Mpx (1080P)
Visual Angle	Horizontal 140° wide angle
Light Vision	IR-CUT (Colorful at daytime, black and white at night)
Extended Memory	TF card with unlimited capacity
Intercom	Full duplex voice intercom
Other Functions	Motion detection; Playback; Take picture/video; Unlock remotely
User Capacity	1000
Common User	988
Visitor User	10
Manic User	2
PIN Length	4~6 digits
Proximity Card Reader	EM or Mifare
Radio Technology	125KHz/13.56MHz
Lead Range	2~6cm
Wiring Connections	Relay output, exit button, alarm, door contact, Wiegand input/output
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0~99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
Wiegand Interface	EM card version: Wiegand 26~44 bits input & output (Factory default: 4 bits, 8 bits (ASCII), 10 digits Virtual Number) Mifare card version: Wiegand 26~44 bits input & output (Factory default: 4 bits, 8 bits (ASCII), 10 digits Virtual Number)
Wiegand Output	
Operating Voltage	DC 12V
Idle Current	≤ 150mA
Active Current	≤ 250mA
Environment	Indoor
Operating Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	0%RH ~ 86%RH
Physical	Zinc-Alloy
Color	Sliver & Black
Dimensions	L145 x W68 x H25 (mm)
Init Weight	450g
Shipping Weight	550g

[www.luchismart.com](http://www.luchismart.com)



USA: +12532990521



NIG: +23418880441



Sales@luchismart.com